

AIR QUALITY SUMMARY 2011

1.0 NITROGEN DIOXIDE DIFFUSION TUBES – WINCHESTER CITY CENTRE

| LOCATION | GRID REF (SU) | 2011 AVERAGE BIAS CORRECTED | | PERCENTAGE CHANGE FROM 2010 |
|---------------------------|---------------|-----------------------------|-----------------------|-----------------------------|
| | | UG/M3 | Percentage Collection | |
| Site 1, 10 Eastgate St | 48563 29391 | 42.1 | 55.6 | 12.3 |
| Site 2, Greyfriars 3 | 48566 29560 | 38.4 | 100.0 | 2.8 |
| Site 3, Friarsgate | 48426 29523 | 31.8 | 100.0 | -6.7 |
| Site 4, Upper Brook St | 48227 29504 | 40.6 | 100.0 | -2.9 |
| Site 5, Roadside Monitor | 48213 29504 | 46.8 | 100.0 | -2.0 |
| Site 6, Roadside Monitor | 48213 29504 | 47.1 | 100.0 | -2.3 |
| Site 7, Roadside Monitor | 48213 29504 | 46.9 | 100.0 | 2.7 |
| Site 8, St Georges St | 48106 29541 | 59.2 | 100.0 | -2.0 |
| Site 9, St Georges St Lad | 48163 29512 | 71.5 | 100.0 | 27.5 |
| Site 10, Jewry St | 48046 29692 | 62.5 | 66.7 | 26.8 |
| Site 11, Southgate St | 47918 29413 | 46.6 | 100.0 | 11.2 |
| Site 12, Sussex St | 47804 29741 | 38.5 | 100.0 | -3.3 |
| Site 13, City Road | 47963 29875 | 41.4 | 100.0 | 3.3 |
| Site 14, 74 Northwalls | 48234 29794 | 45.5 | 100.0 | -1.3 |
| Site 15, Wales St | 48842 29820 | 31.7 | 88.9 | -11.0 |
| Site 16, Alresford Rd | 49557 29437 | 37.4 | 88.9 | 6.6 |
| Site 17, Chesil St | 48679 29068 | 46.2 | 100.0 | 3.1 |
| Site 18, Stockbridge Rd | 47534 30006 | 27.6 | 88.9 | -3.9 |
| Site 19, Andover Rd | 47745 30456 | 34.8 | 77.8 | 6.4 |
| Site 20, Worthy Rd 1 | 48092 30411 | 33.0 | 100.0 | -3.9 |
| Site 21, Worthy Rd 2 | 48092 30411 | 33.9 | 100.0 | -1.5 |
| Site 22, Worthy Rd 3 | 48092 30411 | 32.7 | 100.0 | 0.8 |
| Site 23, St Cross Rd | 47842 29050 | 40.1 | 100.0 | 4.2 |
| Site 24, Romsey Rd | 47495 29511 | 63.3 | 100.0 | 2.6 |
| Site 25, Andover Rd | 47898 30065 | 40.2 | 77.8 | 5.3 |
| Site 26, Bus Station | 48427 29401 | 43.1 | 88.9 | -0.3 |

RED = Exceeds air quality objective

2.0 NITROGEN DIOXIDE DIFFUSION TUBES – DISTRICT WIDE STUDY 2011

| | | | | | | | | |
|--|----------------|--------------------|------------------------|-------------------------|----------------|----------------|---------------------------|-----------------|
| GRID REF'S (SU) | 49443 28927 | 46537 24704 | 46659 24655 | 46414 24279 | 46030 23672 | 45920 23331 | 45505 22345 | 46694 24642 |
| LOCATION F= Building Façade R = Roadside location | Twyford (F) | Otterbourne (R) | Kings Worthy (F) | New Alresford (R) | Denmead (R) | Wickham (R) | Bishops Waltham (R) | Whiteley (R) |
| %AGE COLLECTION | 88.9 | 100.0 | 100.0 | 88.9 | 77.8 | 100.0 | 100.0 | 44.4 |
| BIAS CORRECTED in ug/m3 | 33.4 | 35.8 | 28.8 | 36.9 | 23.2 | 34.2 | 37.3 | 31.3 |
| Percentage change from 2010 | -3.2 | 5.5 | 1.1 | 4.5 | 1.0 | 0.4 | 5.7 | -1.7 |

3.0 REAL TIME AIR QUALITY DATA - WINCHESTER CITY CENTRE

3.1 Short Term Air Quality Objectives

| Year | Exceedances of Air Quality Objective | | | | | |
|--|--|----------|---|----------|--|----------|
| | PM ₁₀ 50ug/m ³ (24 Hr Mean) | | NO ₂ 200ug/m ³ (1 Hr Mean) | | CO 10mg/m ³ (8hr running mean) | |
| | Background | Roadside | Background | Roadside | Background | Roadside |
| 1997 | 8 | 22 | 0 | 299 | 0 | 0 |
| 1998 | 5 | 14 | 0 | 6 | 0 | 0 |
| 1999 | 1 | 3 | 0 | 8 | 0 | 0 |
| 2000 | 2 | 18 | 0 | 15 | 0 | 0 |
| 2001 | 3 | 16 | 0 | 12 | 0 | 0 |
| 2002 | 2 | 21 | 0 | 161 | 0 | 0 |
| 2003 | 21 | 20* | 0 | 70 | 0 | 0 |
| 2004 | Not enough data | 17 | 0 | 0 | 0 | 0 |
| 2005 | 8 | 13 | 1 | 6 | NA | 0 |
| 2006 | 8 | 15 | 0 | 0 | NA | 0 |
| 2007 | 10 | 15 | 0 | 0 | NA | 0 |
| 2008 | 5 | 9 | 0 | 0 | NA | 0 |
| 2009 | 1 | 3 | 0 | 3 | N/A | N/A |
| 2010 | 1 | 4 | 0 | 0 | N/A | N/A |
| 2011 | 3 | 9 | 0 | 0 | N/A | N/A |
| Pass = less than 35 failures/year | | | Pass = less than 18 failures/year | | Pass = No failures of objective | |
| Numbers in red FAILED the short term mean air quality objectives | | | | | | |

3.2 Long Term Air Quality Objectives

| Year | Compliance with Annual Mean Air Quality Objectives | | | | | |
|------|---|----------|--|----------|---|----------|
| | Mean PM ₁₀ in ug/m ³ 40ug/m ³ (Annual Mean) | | Mean NO ₂ in ug/m ³ 40ug/m ³ (Annual Mean) | | Mean CO in mg/m ³ No annual objective | |
| | Background | Roadside | Background | Roadside | Background | Roadside |
| 1997 | 18.4 | 26.5 | 35.30 | 82.7 | 0.7 | 1.3 |
| 1998 | 17.2 | 21.9 | 39.7 | 58.1 | 0.5 | 1.3 |
| 1999 | 17.6 | 21.1 | 31.1 | 60.2 | 0.5 | 1.2 |
| 2000 | 16.4 | 21.2 | 33.0 | 68.6 | 0.5 | 1.2 |
| 2001 | 14.8 | 27.3 | 33.4 | 50.8 | 0.3 | 1.2 |
| 2002 | 19.8 | 28.9 | 27.3 | 65.5 | 0.3 | 1.0 |
| 2003 | 25.7 | 31.6 | 41.1 | 55.8 | 0.3 | 1.0 |
| 2004 | Not enough data | 29.8 | 29.4 | 52.1 | 0.3 | 0.8 |
| 2005 | 21.3 | 28.1 | 26.2 | 53.5 | NA | 0.5 |
| 2006 | 20.0 | 27.0 | 28.0 | 51.0 | NA | 0.5 |
| 2007 | 19.0 | 25.0 | 27.0 | 51.0 | NA | 0.5 |
| 2008 | 18.0 | 22.0 | 27.0 | 48.0 | NA | 0.4 |
| 2009 | 18.0 | 21.0 | 26.0 | 48.0 | NA | NA |
| 2010 | 17.0 | 22.0 | 27.0 | 50.0 | NA | NA |
| 2011 | 20.0 | 27.0 | 26.0 | 46.0 | NA | NA |

Numbers in red FAILED the annual mean objective

5.0 TECHNICAL NOTES

5.1 Diffusion Tube Data

All diffusion tubes were from Gradko and used a mixture of 20 Percent TEA in water. This is the third year that this formulation has used as in accordance with DEFRA recommendations.

The results have been adjusted by using a locally generated bias correction factor using the procedure detailed in the new DEFRA guidance document Technical Guidance LAQM TG(09). This was calculated by locating three diffusion tubes adjacent to the roadside real time analyser and comparing results. The local bias correction calculated for 2011 was 1.02, which is very similar to 1.03 calculated for 2010. The national bias correction factor for Gradko 20 Percent TEA in water produced by DEFRA is lower at 0.9 but 1.02 is within the spread of results obtained at other locations.

Two of the sites have triplicate samples to investigate precision of the tubes. The data for 2011 shows all sites have good precision with coefficients of variation for all sampling periods and locations being less than 20 percent with an average of less than 10 percent (0.3 and 1.9 for the two triplicate sites).

The Town Centre diffusion tubes have been located to represent nearest relevant public exposure locations i.e. domestic building facades. To save money a few sites have been dropped from the study. These are:

- Triplicate samples at Greyfriars dropped, two other triplicate sites kept
- Jewry St – One of two sampling sites, site with highest average kept
- Southgate St - One of two sampling sites, site with highest average kept
- Northwalls - One of two sampling sites, site with highest average kept
- Romsey Rd Hillier's - Always well below air quality objective as some distance from road.

The District wide diffusion tube survey continued this year using the same sites as for the last two year; except for the removal of the Hursley site which was well below the air quality objective. The study is a mix of roadside sites and nearest domestic building facades. In general the older sites were roadside locations and these have been maintained in order to ensure consistency in data trends. The new sites have been located at distances representing the nearest domestic building façade in the study area.

5.2 Real Time Monitoring Results

The roadside site is located 2.75 metres from the kerb on St Georges St (Grid Ref SU 48506 29525) whilst the urban background site is located 18 metres from the kerb off Friarsgate (Grid Ref SU 48213 29504). The background site samples at a height of 2.80 metres and the roadside site at 2.65 metres. New instruments (like for like) were installed in March 2005.

Particle results still use an unheated BAM 1024 analyser and have therefore had a correction factor applied as now recommended, data being divided by 1.2. All data from previous years has now had the same correction factor applied. Data collection efficiency for all instruments in 2011 was greater than 90 percent. The lowest collection efficiency was for the roadside nitrogen dioxide results at 91 percent. This

was due to the failure of the air conditioning unit in the summer (June 11) which had to be fully replaced. During this period the analyser had to be turned off as the temperature in the cabinet was too high for the instruments tolerance.

All results have been zero and spanned corrected with readings taken approximately every 2 weeks in accordance with DEFRA guidance. All gases used for calibration have been independently certified. All instruments are fully serviced every six months by external contractors.

All data was ratified by an external air quality consultant (AQDM).

6.0 SUMMARY OF RELEVANT AIR QUALITY OBJECTIVES

| Pollutant | Air Quality Objective | | Date to be achieved by |
|---|---|-----------------------------------|------------------------|
| | Concentration | Measured as | |
| Carbon monoxide | 10.0mg/m ³ | Maximum daily running 8 hour mean | 31.12.2003 |
| Nitrogen dioxide (Provisional) | 200µg/m ³ not to be exceeded more than 18 times a year | 1 Hour mean | 31.12.2005 |
| | 40µg/m ³ | Annual mean | 31.12.2005 |
| Particles (PM ₁₀) (Gravimetric) | 50µg/m ³ not to be exceeded more than 35 times a year | 24 hour mean | 31.12.2004 |
| | 40µg/m ³ | Annual mean | 31.12.2004 |

7.0 DISCUSSION

7.1 Nitrogen dioxide – Winchester City Centre

Both real time sites are in compliance with the 24 hour mean objective but as in previous years only the background site complies with the annual mean objective.

The diffusion tube results show that there are still areas adjacent the main roads within the Air Quality Management Area (AQMA) that fail to meet the 2005 annual mean objective. These failures are spatially concentrated within the one way system around the town centre.

The diffusion tubes are located on building facades, therefore the nearer the buildings are to the road, the higher the results.

The current average trend in recent years appears to be mainly flat with no significant evidence of an overall improvement or degradation in air quality. It is noted that there has been a large increase in two locations (Jewry St and one of the two sites on St Georges St) which remains unexplained. Future monitoring will indicate if this increase continues at these locations.

7.2 Nitrogen dioxide – District

In 2011 all sites were in compliance with the annual mean objective giving similar overall results to 2010.

7.3 Particles (PM₁₀) – Winchester Town Centre

All sites are in compliance with both the current 24 hour and annual objectives. It is considered that there is now sufficient evidence to show overall compliance with the air quality objectives for PM₁₀ and a detailed assessment report has now been submitted and accepted by DEFRA recommending that Winchester undeclare the air quality management area (AQMA) with regards to this parameter. However,

monitoring will continue to at least the end of 2012 to provide further reassurance regarding this conclusion.

7.4 Carbon monoxide – Winchester Town Centre

Monitoring no longer performed.