

## SPECIFICATIONS FOR SOUTHWICK PARISH NAMEPLATES

| PARAMETER              | SPECIFICATION   |
|------------------------|---|
| LOCATION               |   |
| NO. OF PLATES REQUIRED |   |
| MATERIALS              | Cast aluminium  |
| FONT                   | Kindersley  |
| LETTERING COLOUR       | Cream   |
| LETTERING HEIGHT:      | Upper Case: 87mm<br>Lower Case: 63mm 'x' height   |
| ADDITIONAL LETTERING   | "leading to", "inclusive", " <i>numerals</i> " will be lower case with a height of 35mm   |
| SECONDARY NAMES        | 49mm  |
| BORDER SIZE            | 25mm  |
| BORDER COLOUR          | Cream   |
| BACKGROUND COLOUR      | Blue  |
| REVERSE COLOUR         | Cream   |
| SYMBOLS                | 'No Through Road' "T" to diagram 816.1  |
| FINISH                 | All corners are smooth and catch free   |
| STRENGTHENING          | Aluminium channel 20mm fixed at 150mm centres   |
| FITTINGS               | Fitted with retaining pins and set in the ground 300mm deep with a 150mm surround of concrete. Posts will not project above the top of the nameplate.                       |
| STAND                  | 60mm diameter aluminium posts having a wall thickness of 3.5mm, manufactured from HE30TF alloy to BS1474 and anodized 25 microns thick to BS1625. Tops sealed with PVC caps |
| STAND COLOUR           | Dyed grey to BS873  |
| POSITION OF SIGN       | Top edge of plate 1m above ground level   |
| DIAGRAM                |   |

