

SPECIFICATIONS FOR CONSERVATION AREA NAMEPLATES

PARAMETERS	CONSERVATION AREAS
LOCATION	
NO. OF PLATES REQUIRED	
MATERIALS	Cast aluminium
FONT	Kindersley
LETTERING COLOUR	Black
LETTERING HEIGHT:	Upper Case: 87mm Lower Case: 63mm 'x' height
ADDITIONAL LETTERING	"leading to", "inclusive", " <i>numerals</i> " will be lower case with a height of 35mm
SECONDARY NAMES	49mm
BORDER SIZE	25mm
BORDER COLOUR	Black
BACKGROUND COLOUR	White
REVERSE COLOUR	Black
SYMBOLS	'No Through Road' "T" to diagram 816.1
FINISH	All corners are smooth and catch free
STRENGTHENING	Aluminium channel 20mm at 150mm centres
FITTINGS	Fitted with retaining pins and set in the ground 300mm deep with a 150mm surround of concrete. Posts will not project above the top of the nameplate.
STAND	60mm diameter aluminium posts having a wall thickness of 3.5mm, manufactured from HE30TF alloy to BS1474 and anodized 25 microns thick to BS1625. Tops sealed with PVC caps
STAND COLOUR	Dyed grey to BS873
POSITION OF SIGN	Top edge of plate 1m above ground level
DIAGRAM	

